

## **Certificate of Conformity**



Global-Mark Pty Ltd, Suite 4.07, 32 Delhi Road, North Ryde NSW 2113, Australia

Tel: +61 (0)2 9886 0222 - <u>www.Global-</u> Mark.com.au

#### Certificate Holder: Koppers Performance

Chemicals Australia Pty Ltd Level 5, 53 Walker Street, North Sydney NSW 2060 Australia Tel: 1800 088 809 www.kopperspc.com.au

	Certificate number: CM30093 Rev4
--	----------------------------------

#### THIS IS TO CERTIFY THAT

## LVL Glueline treated with DeterMite®100

#### Type and/or use of product:

Volume 1 - B1P1 (1) & (2)o

LVL Wood Framing to be used in residential and commercial applications, south of the Tropic of Capricorn, where:

- Exposure Conditions: Internal, above ground applications only
- Service Conditions: Protect from the weather and wetting, no leaching
- Hazard Type: Termites and Borers.

## **Description of product:**

LVL Glueline treated with DeterMite®100 made of any combination of Karri, Jarrah and Softwood veneers with thickness up to 4.8mm

1, 2, 3, 4, 5, 6, 7, 8, 9 & 10

	<b>BCA (2022)</b>					
	Volume One		Volume Two and H	Volume Two and Housing Provisions		
Performance Requirement(s)	B1P1(1) & (2)o	Structural reliability	H1P1 (1) & (2)o	Structural reliability and resistance		
Deemed-to-Satisfy Provision(s):						
State or territory variation(s):			QLD H1P3	Termite management measures		
SUBJECT TO THE FOLLOW	ING LIMITATIONS AND	CONDITIONS AND THE PRODUCT	TECHNICAL DATA IN APPENDIX A	AND EVALUATION ST	ATEMENTS IN APPENDIX B	
Limitations and conditions:					fication/s:	

Scope of certification: The CodeMark Scheme is a building product certification scheme. The rules of the Scheme are available at the ABCB website www.abcb.gov.au. This Certificate of Conformity is to confirm that the relevant requirements of the Building Code of Australia (BCA) as claimed against have been met. The responsibility for the product performance and its fitness for the intended use remain with the certificate holder. The certification is not transferrable to a manufacturer not listed on Appendix A of this certificate.

Disclaimer: The Scheme Owner, Scheme Administrator and Scheme Accreditation Body do not make any representations, warranties or guarantees, and accept no legal liability whatsoever arising from or connected to, the accuracy, reliability, currency or completeness of any material contained within this certificate; and the Scheme Owner, Scheme Administrator and Scheme Accreditation Body disclaim to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this certificate.

The purpose of Global-Mark construction site audits is to confirm the practicability of installing the product; and to confirm the appropriateness and accuracy of installation instructions

In placing the CodeMark mark on the product/system, the certificate holder makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product

Herve Michoux
Global-Mark Managing Director

Peter Gardner P. Cardoo Unrestricted Building Certifier

certified herein. In issuing this Certificate of Approval Global-Mark has relied on the expertise of external bodies (laboratories, and technical experts).

Volume 2 - H1P1 (1) & (2)o

Date of issue: 08/05/2024

Date of expiry: 22/11/2024





Certificate number: CM30093 This certificate is only valid when reproduced in its entirety.



## **Certificate of Conformity**

Limited to termite action (and also borers)

#### APPENDIX A – PRODUCT TECHNICAL DATA

### A1 Type and intended use of product

See page 1 of this certificate: Type and/or use of product.

Typical uses are as interior beams, interior framing, Wall and subfloor, staircases, stringers, trusses, joists.

## **A2** Description of product

See page 1 of this certificate: Description of product.

#### A3 Product specification

See page 1 of this certificate: Description of product.

The LVL products must be bonded with a phenol-formaldehyde (PF)-based adhesive containing the required DeterMite®100 loading. It must be applied between each veneer layer evenly to achieve a minimum loading of 0.0023% mass/mass of bifenthrin based on the oven-dried mass of the treated product.

The LVL products must be marked in accordance with Wesbeam 'e2S' Glueline Termiticide Treated LVL Rev 1.02 dated 22/06/2018

## A4 Manufacturer and manufacturing plant(s)

Wesbeam

190 Pederick Rd

Neerabup, WA 6031

## A5 Installation requirements

See page 1 of this certificate: Type and/or use of product.

#### A6 Other relevant technical data

Certificate number: CM30093

Any referenced documents within the technical literature identified in Appendix A, A3 and Appendix A, A5.



# **Certificate of Conformity**

#### **APPENDIX B – EVALUATION STATEMENTS**

## **B1** Evaluation methods

The following assessment methods have been used to determine compliance with NCC 2019 including Amendment 1:

Code Clause	Assessment Method(s)	Evidence of suitability	Evidence reference in B2
B1P1(1) & (2)o	A2G2 (2) (b)(ii) & (c)	A5G3 (1) (f) – Another form of documentary evidence	Items 1, 2 & 3
H1P1(1) & (2)o	A2G2 (2) (b)(ii) & (c)	A5G3 (1) (f) – Another form of documentary evidence	Items 1, 2 & 3
QLD H1P3	A2G2 (2) (b)(ii) & (c)	A5G3 (1) (f) – Another form of documentary evidence	Items 1, 2 & 3

## **B2** Reports

The following reports have been used as evidence to determine compliance with NCC 2019 including Amendment 1:

Ref	Author	Reference	Date	Description	NATA Registration
1	Hague, J.R.B.	Agreement No: 20151108	August 2017	Hazard Class H2 field trial to determine the above-ground performance of karri Laminated Veneer Lumber, glueline- and envelope-treated with bifenthrin, against attack by <i>Coptotermes acinaciformis</i> . Australian Forest Research Company; Confidential Client Report dated August 2017. 17 pp.	Independent Testing Authority (www.afrcpl.com.au). Note: There are no JAS-ANZ accredited laboratories able to undertake field testing of preservative- treated products against termites.
2	APVMA	Label approval No: 83996/112813	03/04/2018	To extend use to include protection against termites (excluding <i>Mastotermes darwiniensis</i> ) in the treatment of not thicker than 4.8 mm hardwood veneer in plywood and Laminated Veneer Lumber (LVL) in hazard class H2 for all areas south of the Tropic of Capricorn.	Not applicable.
3	J. Carr, D.K Scown and J.W Creffield	ENSIS Report ID No 6193	April 2007	Resistance of rubberwood plywood, treated with bifenthrin by glueline addition, to attack by lyctine beetles.	Not applicable.

The Certificate Holder has chosen not to make the above identified evidence of compliance publicly available, due to the documents being considered commercial in confidence.